

Why do projects go wrong and what systemic risks exist in the current design process?

Tailings

Presenter: David Pearce, General Director - SRK

Location: Webinar



- Brumadinho, Brazil, January 2019
- Samarco, Brazil, November 2015
- Mt Polley, Canada, August 2014
- Kolontár, Hungary, October 2010
- Baie Mare, Romania, 2000
- Aznacollar, Spain, 1999



Possible events include:

- Loss of integrity; no loss of material or discharge
 - Potentially reduces production until dam repaired / alternative sites constructed ~3-6 months
- Over-topping during storm event
 - Could erode dam wall leading to failure
 - Release of chemicals into environment
- Material discharge; locally contained
 - Investigation by Rostekhnadzhor could lead to cessation of operations and fines
- Material discharge which affects community
 - Clean-up liabilities
 - Fines
- Catastrophic failure
 - Loss of life
 - Imprisonment for managers
 - Loss of business



All can have a significant impact on the project success and potentially on corporate reputation


- Cadia dam failure in March 2018 did not result in any external discharges but reduced share value by \$1 billion

If there have not been any failures in Russia, does that mean all is well?


- We are aware of several major failures, though fortunately they “only” resulted in the tailings dam becoming unusable
- We are also aware of several tailings facilities which have been condemned
 - Excessive water content – operating without a “beach”
 - Rate of lift exceeds design norms
- International best practice has moved on:
 - Russian guidelines consider Effective Stress Analysis (ESA) only.
 - International Guidelines also consider Undrained Stress Analysis (USA) be used in design, particularly for all upstream dams. This assesses the risk of liquefaction which could be triggered by seismic or static loading.
 - International Factor of Safety is higher

	Loading Condition	Shear strength used for evaluation	Minimum FoS (International guidelines)	Minimum FoS (Russian guidelines)
1	Long term drained	Effective strength	1.5	1.25
2	Pseudo-static	Consolidated undrained strength (Loading condition 1, repeated including horizontal acceleration)	1.0	
3	Post-seismic / Liquefaction	Post-seismic shear strength within the tailings mass	1.0-1.3	


- Principal options:
 - Valley fill
 - Ring fill
 - Backfill
 - Subaqueous



- Three main dam designs:
 - Downstream
 - Centreline
 - Upstream



(a) Downstream Method




(b) Centreline Method



(c) Upstream Method

- Maintain beach to allow coarse tailings to settle and keep phreatic surface from wall
 - Ensures next lift has a firm foundation
 - Cease deposition or move discharge points if heavy rain floods beach
- Ensure drains are working
- Do not increase height faster than the tailings can compact and drain



Courtesy of AngloAmerican

- Monitoring – piezometers, inclinometers, pressure gauges, remote sensing
- Inspections
- Annual Dam safety inspections by an external engineer of record
- Third party reviews at least every three years
- Internal governance reviews
- Independent tailings review boards - to conduct a third-party review of design, operation, surveillance and maintenance

Risk assessments - if there was a failure, what could happen?

- Consider potential impact
- Several standards (ICOLD; ANCOLD)
- Ensure controls are appropriate for risk
- Consider redesigning or relocating TSF if necessary

Damage type	Minor	Medium	Major	Catastrophic
Infrastructure (dam, houses, commerce, farms, community) USD\$	<\$10M	\$10M-\$100M	\$100M-\$1B	>\$1B
Business importance	Some restrictions	Significant impacts	Severe to crippling	Business dissolution, bankruptcy
Public health	<100 people affected	100-1000 people affected	<1000 people affected for more than one month	>10,000 people affected for over one year
Social dislocation	<100 person months or <20 business months	100-1000 person months or 20-200 business months	>1000 person months or >200 business months	>10,000 person months or numerous business months
Impact area	<1 km ²	<5 km ²	<20 km ²	>20 km ²
Impact duration	<1 (wet) year	<5 years	<20 years	>20 years
Impact on natural environment	Damage limited to items of low conservation value. Remediation possible.		Significant effects on rural land and local flora & fauna. Limited effects on: A. Items of local & state natural heritage B. Native flora and fauna within forestry, aquatic and conservation reserves	Extensive rural effects. Significant effects on river system and areas A & B. Limited effects on: C. Items of National or World natural heritage D. Native flora and fauna within national parks. Remediation difficult

Population at Risk	Severity of Damage and Loss			
	Minor	Medium	Major	Catastrophic
<1	Very Low	Low	Significant	High C
>1 to 10	Significant (note 2)	Significant (note 2)	High C	High B
>10 to 100	High C	High C	High B	High A
>100 to 1,000	Note 1	High B	High A	Extreme
>1,000		Note 1	Extreme	Extreme

- Key design issues behind disasters:
 - Design overlooked weak foundation
 - Water balance not verified / insufficient allowance for peak events
 - Lack of emergency spillway
 - Insufficient drainage installed
 - Inappropriate design
- Key operational issues behind disasters:
 - Beach allowed to be flooded or smaller than designed resulting in fine tailings being deposited near crest
 - Rate of rise is excessive
 - Drains not maintained / not identified as being inadequate
 - Not reacting when phreatic surface is noted as being too high

- Legacy issues
 - TSF constructed many years ago when standards were less strict and techniques less detailed
- Familiarity
 - Routine activity allows complacency to develop
- Production pressures
 - Temporarily allow beaches to be flooded
- Lack of internal expertise / awareness
 - TSF managed by processing specialists, not TSF specialists
- Budget & time constraints during design process
 - Insufficient data collected / analysis done

- Strength parameters used in some locations are not consistent with expected properties for similar materials and require verification.
 - SRK recommends resampling and retesting with ASTM and/or BS standards
- Stability analysis does not include all loading scenarios included in international guidelines.
 - Pseudo-static and post-seismic/liquefaction stability loading scenarios have not been analyzed
- Preference is for upstream dams
- Lower Factor of Safety permitted in Russia
- Many sites now much larger than was typical when the regulations were developed
- Lack of emergency spillway at most sites
 - Emergency spillways are used for emergency situations, not for discharging supernatant during regular operations. Should be capable of handling a 1-in-1000 year, 72 hour flood event
- The TSFs are not lined and therefore there is potential for seepage of tailings effluent water.
- The standard of monitoring has fallen behind current best practice – stand pipes vs vibrating-wire piezometers; no slope inclinometers; etc. - which reduces the depth of analysis possible.
 - Monitoring is focused on collecting data for compliance; not for proactive investigation
- No independent reviews
 - Annual review typically done by designers

Design stage

- Ensure design is independently reviewed by specialists familiar with international standards
- Verify material parameters to ASTM and/or BS standards
- Review risks and Factor of Safety using both ESA and USA methods
- Independent reviews

Operations

- Upgrade monitoring system and provide internal reports which focus on risk potential
 - Record beach width, continuous monitoring with piezometers
- Third party reviews at least every three years
- Internal governance reviews or Independent tailings review boards depending on risk

Copyright and Disclaimer

Copyright (and any other applicable intellectual property rights) in this document and any accompanying data or models which are created by SRK Consulting (Russia) Limited ("SRK") is reserved by SRK and is protected by international copyright and other laws. Copyright in any component parts of this document such as images is owned and reserved by the copyright owner so noted within this document.

The use of this document is strictly subject to terms licensed by SRK to the named recipient or recipients of this document or persons to whom SRK has agreed that it may be transferred to (the "Recipients"). Unless otherwise agreed by SRK, this does not grant rights to any third party. This document shall only be distributed to any third party in full as provided by SRK and may not be reproduced or circulated in the public domain (in whole or in part) or in any edited, abridged or otherwise amended form unless expressly agreed by SRK. Any other copyright owner's work may not be separated from this document, used or reproduced for any other purpose other than with this document in full as licensed by SRK. In the event that this document is disclosed or distributed to any third party, no such third party shall be entitled to place reliance upon any information, warranties or representations which may be contained within this document and the Recipients of this document shall indemnify SRK against all and any claims, losses and costs which may be incurred by SRK relating to such third parties.

SRK respects the general confidentiality of its potential clients' confidential information whether formally agreed with them or not and SRK therefore expects the contents of this document to be treated as confidential by the Recipients. The Recipients may not release the technical and pricing information contained in this document or any other documents submitted by SRK to the Recipients, or otherwise make it or them available to any third party without the express written consent of SRK.

© SRK Consulting (Russia) Limited 2020

version: September 2020